



MAKING THE DIFFERENCE
TO YOUR VISITOR EXPERIENCE



LoopDVP-HD

High Definition Digital Video Player on
Flash Card

Reliable

Storage on Flash Card. No moving parts.

Quality

Digital H264/MPEG2/4 high quality video up to 1080P.

Simple

Load video files onto flash card and the LoopDVP HD will play them directly in a constant loop at power on.

Audio

High quality stereo line out.

Comprehensive Connectivity

HDMI, VGA, DVI, and Component mean complete flexibility when cabling.

Economic

Quick and easy for technicians to install - you plug, it plays!

Compact

Compact stand alone enclosure.

The LoopDVP HD is a High Definition Digital Video Player which uses flash memory cards. The total absence of mechanical parts in its design guarantees absolute reliability.

One of the most common applications for HD flash video players is playing one video in a loop. This application requires no control mechanism, and no configuration. Plug and play in it's simplest form - you plug, it plays. The player can play H264 and MPEG2/4 files up to FullHD 1080P.

A cost-effective solution for simple installations which will save both time and effort for technicians by reducing the unused control modules found in alternative players.



www.rsf-int.com

Made in Europe

Reliability... **EXTREME**

- Designed for 24/7 operation
- Fully solid state with no moving parts

Warranty... **EXTREME**

- 8 year warranty exchange for clients ordering from a registered dealer

Technical specifications

Audio/video Parameters

| | |
|----------------------|---|
| Files decoded | H264/MPEG-4 part10 transport streams with AAC audio, MPEG2, MPEG1 BMP, JPEG, MP2, MP3, WAV, WMA, AC3 stereo, AC3 5.1 pass through |
| HDMI Resolution | 1080P, 1080i, 720p, 576p, 480p, 1360x768, 1024x768 |
| Component Resolution | 1080i, 720p, 576p, 480p |
| VGA Resolution | 1360x768, 1024x768 |
| Maximum bit rate | 30MB/s |

Connectors

| | |
|-----------------|---|
| Video outputs | HDMI, DVI (with adapter), VGA, Component (with adapter) |
| Audio outputs | Stereo line out |
| Flash card Slot | 1 slot on front panel |
| Storage | SD and SDHC (class 4 or 6) |

Indicators

| | |
|-------------------|-------|
| Power indicator | 1 Led |
| Reading indicator | 1 Led |
| Update indicator | 1 Led |
| Error indicator | 1 Led |

Power supply 5v DC

Maximal consumption 3A

Enclosure stand alone enclosure

Dimensions (enclosure) 50 x160 x 30 mm (WxDxH)

Environment

| | |
|-------------|----------------------------|
| Temperature | 0°C (32°F) to 50°C (122°F) |
| Humidity | 0-90% |

Warranty 8 years

Connections



Front



Back



Commercial Division
RSF Europe sa
10b, route d'Arlon
L-7471 Saeul
G.D. of Luxembourg

Tel. +352 49 74 20 40
Fax +352 49 74 20 50
info@rsf-int.com

Manufacturer
RSF
45, Av. Marcel Dassault
31500 Toulouse
France

Tel. +33 5 61 20 79 09
Fax +33 5 61 80 00 94

www.rsf-int.com

Made in Europe